

ORION-450AX

450W Auto-range input PS/2 ATX power supply



SPECIFICATION

Input Voltage	90V ~ 132V, 180V ~ 264V AC Auto-range
Input Frequency	47 ~ 63 Hz
Input Current	7A@115V, 4A@230V
Efficiency	> 70%
Holdup Time	16.7 ms. at full load
Over Voltage Protection	+5V: 5.6 ~ 6.5V; +3.3V: 4.0 ~ 4.5V; +12V: 13.5 ~ 15.5V
Over Power/Load Protection	Output power over 110% ~ 150%
MTBF	80,000 hrs
EMI & Safety Approval	UL, cUL, TUV, CE, FCC
Temperature/Humidity	Operating: 0 ~ 40°C, 10 ~ 90%RH Storage: -60 ~ 70°C, 5 ~ 95%RH
Dimension (WxDxH)	150x140x86 mm; 5.9"x5.5"x3.4"

FEATURES

- PS/2 ATX power supply suitable for 2U and up chassis
- Auto-range AC input
- 450W output suitable for heavy loading systems

ORDERING GUIDE

- **ORION-450AX**
450W Auto-range input PS/2 ATX power supply

DC OUTPUT

	+5	+3.3V	+12V	-5V	-12V	+5Vsb
Max. Load	40A	28A	17A	0.5A	1.5A	1A
Min. Load	2A	0A	0.2A	0A	0A	0A
Max. Watt.	225W	225W	204W	2.5W	18W	5W
Load Reg.	±5%	±2%	±5%	±5%	±10%	±5%
Ripple	±1.2%	±1.5%	±1%	±1.2%	±1%	±2%
Noise	±1.2%	±1.5%	±1%	±1.2%	±1%	±2%